

# DX850e

## LABEL DISPENSER



**NEW!**

### Primera's new DX850e Label Dispenser helps you quickly and easily peel and present labels from rolls.

The built-in precision micro-switch detects when a label has been removed. Then, the next label is quickly and automatically fed forward, ready to remove. You'll be able to apply labels much more quickly than ever before. A built-in LED display counts up or down, indicating how many labels you've applied or how many you have left.

**PRIMERA**  
TECHNOLOGY, INC.



## Fast and Easy Label Dispensing

The DX850e Label Dispenser automatically peels and presents self-adhesive labels one at a time. It replaces manual label peeling, making your production lines faster and more efficient.

DX850e is robust and reliable, made in the USA of heavy-duty sheet metal and machined steel. It is also one of the few label dispensers available with UL, UL-C, CE listings, FCC approval and RoHS compliance.

## Features

- » Easy to use – no screws or clamps to adjust
- » Full range of motion – left or right justification of labels is not necessary; operator can adjust to the most convenient position
- » High-precision, reliable micro-switch activation – nothing to clean or get dirty; works with virtually any label including clear labels
- » LED display – with built-in up/down counter for labels dispensed
- » Universal Power Supply – simply change line cord for use in any country



## Specifications

|                               |   |
|-------------------------------|---|
| <b>Supply roll diameter:</b>  | Up to 203 mm (8")   |
| <b>Media liner width:</b>     | 25.4 mm to 213 mm (1.00" to 8.38")  |
| <b>Label height/length:</b>   | 19.1 mm to 609.6 mm (0.75" to 24")  |
| <b>Supply roll core:</b>      | 50.8 mm to 76.2 mm (2" to 3")   |
| <b>Label width:</b>           | 19.1 mm to 209.6 mm (0.75" to 8.25")  |
| <b>Electrical rating:</b>     | 12 VDC, 5.0 A   |
| <b>Power requirements:</b>    | 100-240VAC, 50/60 Hz, 60 watts  |
| <b>Feed speed:</b>            | 4 in/sec. in Default Mode. 2 in/sec in Half-speed Mode for 6-8" wide labels |
| <b>Agency certifications:</b> | UL, UL-C, CE, FCC Class B   |
| <b>Weight:</b>                | 5.2 kg (11.5 lbs)   |
| <b>Dimensions:</b>            | 341 mmW x 222 mmH x 287,6 mmD<br>(13.44" W x 8.75" H x 11.25" D)            |

**PRIMERA**  
TECHNOLOGY EUROPE™

Mainzer Strasse 131  
65187 Wiesbaden/Germany  
www.primeralabel.eu

Phone: +49 (0)611 92777-0  
Fax: +49 (0)611 92777-50  
E-mail: sales@primera.eu